

# Arocs 4158E6 8x4

# High-Capacity Firefighting Tanker

## PM180/BZ6







### Chassis Technical Specifications

• Manufacturer: Mercedes-Benz Trucks Factory

• Trade Name: Mercedes-Benz Arocs

• Model: Arocs 4158

• Wheel Configuration: 8x4

• Engine: Mercedes-Benz OM471LA.6-55

• Displacement: 15,598 cm<sup>3</sup>

Maximum Power Output: 315 kW (~428 HP)

• Transmission: Automatic

• Steering: Power-assisted

• Braking System: Pneumatic brakes with ABS

• Suspension: Multi-leaf spring suspension

• Tires: 315/80R22.5 (Front & Rear)

• Dimensions (L × W × H): 11,450 × 2,500 × 3,550 mm

• Wheelbase: 1750 + 4600 + 1350 mm

• Curb Weight: 15,000 kg

• Gross Vehicle Weight Rating: 41,000 kg

• Rear Axle Load: 2 × 13,000 kg

Cabin Seating Capacity: 2 (driver included) / crew cabin: 2+4)

• Noise Emission Standard: 88 dB @ 1200 rpm

• Top Speed: 85 km/h

Fuel Consumption: 81.6 L / 100 km

#### **Emissions**

• CO: 0.1594 g/km

NOx: 0.0984 g/km

• HC: 0.0095 g/km

HC+NOx: 0.0999 g/km

• Particles: 0.0002 g/km

#### **Storage Compartments**

• Structure: Full aluminum alloy – rustproof & corrosion-resistant

• Design: Patented welded frame with bolted inner structure

• Advantages: Lightweight, durable, and weather-resistant

• Wiring: Embedded in grooves to prevent wear and damage

#### Tanks

• Material: Polypropylene composite (PP) – corrosion-proof

Total Capacity:

o Water: 14,000 L

o Foam: 4,000 L

### Control System

• Technology: Modular control with PLC (Programmable Logic Controller)

• Operation: Electronic commands with configurable modules

• Protection Level: IP56 or higher

#### Standardized Components (CXFIRE Modular System)

- Water pumps
- Roof-mounted water monitors
- Aluminum rolling shutters
- Storage racks
- Pipe networks

• Benefits: Full compatibility, reliability, and component interchangeability

## Firefighting System

• Main Pump: 170 L/S @ 10 bar

• Roof Monitor flow rate: ≥5000-10000L/min, adjustable

• Paint Color: Firefighter Red























